

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

Xylene mixture of isomers

Creation date 24th August 2016

Revision date 28th May 2025 Version 9.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Xylene mixture of isomers

Substance / mixture substance

Chemical name reaction mass of ethylbenzene and m-xylene and p-xylene

EC (EINECS) number 905-562-9

Registration number 01-2119555267-33-xxxx

Other substance name

Dimethylbenzene, Xylene

1.2. Relevant identified uses of the substance or mixture and uses advised against

Substance's intended use

Chemical production, analytical chemistry, laboratory synthesis, industrial applications.

Substance uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Supplier

Name or trade name Ing. Petr Švec - PENTA s.r.o.

Address Radiová 1122/1, Praha 10, 102 00

Czech Republic

Identification number (CRN)02096013VAT Reg NoCZ02096013Phone+420 226 060 681E-mailinfo@pentachemicals.euWeb addresswww.pentachemicals.eu

Competent person responsible for the safety data sheet

Name Ing. Petr Švec - PENTA s.r.o. E-mail info@pentachemicals.eu

1.4. Emergency telephone number

European emergency number: 112 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the substance in accordance with Regulation (EC) No 1272/2008

The substance is classified as dangerous.

Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (ears) Aquatic Chronic 2, H411

Most serious adverse physico-chemical effects

Flammable liquid and vapour.

Most serious adverse effects on human health and the environment

May be fatal if swallowed and enters airways. Causes skin irritation. May cause damage to hearing organs through prolonged or repeated exposure. May cause respiratory irritation. Causes serious eye irritation. Harmful in contact with skin or if inhaled.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

Xylene mixture of isomers

Creation date 24th August 2016

Revision date 28th May 2025 Version 9.0

2.2. Label elements

Hazard pictogram









Signal word

Danger

Dangerous substance

reaction mass of ethylbenzene and m-xylene and p-xylene

(EC: 905-562-9) **Hazard statements**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways. H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

H335 May cause respiratory irritation.
H373 May cause damage to the ears through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.
P310 Immediately call a POISON CENTER/doctor.

Supplemental information

Restricted to professional users.

2.3. Other hazards

The substance does not have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Substance does not meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients

3.1. Substances

Chemical characterization

The substance specified below.

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
EC: 905-562-9 Registration number: 01-2119555267-33- xxxx	substance main component reaction mass of ethylbenzene and m- xylene and p-xylene		Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (ears) Specific concentration limit: STOT RE 2, H373 (ears): C ≥ 10 %	1



SAFETY DATA SHEET						
	according to Regulation (EC) No 1907/2006 (REACH) a	as amended			
	Xylene mixture of isomers					
Creation date	24th August 2016					
Revision date	28th May 2025	Version	9.0			

Notes

1 Substance of unknown or variable composition, complex reaction products or biological materials - UVCB.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Provide medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Cough, headache. May cause respiratory irritation.

If on skin

Causes skin irritation.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.



SAFETY DATA SHEET					
	according to Regulation (EC) No 1907/2006 (REACH) as amended				
	Xylene mixture of isomers				
Creation date	24th August 2016				
Revision date	28th May 2025	Version	9.0		

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

Storage class 3A - Flammable liquids (flash point below 55 °C)

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL

reaction mass of ethylbenzene and m-xylene and p-xylene					
Workers / consumers Route of exposure Value Effect					
Workers	Inhalation	221 mg/m³	Chronic effects systemic		
Workers	Inhalation	442 mg/m³	Acute effects systemic		
Workers Inhalation 442 mg/m³ Acute effects local					
Workers	Dermal	212 mg/kg	Chronic effects systemic		



SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended Xylene mixture of isomers Creation date 24th August 2016 Revision date 28th May 2025 Version 9.0

reaction mass of ethylbenzene and m-xylene and p-xylene					
Workers / consumers	Route of exposure	Value	Effect		
Consumers	Inhalation	65.3 mg/m ³	Chronic effects systemic		
Consumers	Inhalation	260 mg/m ³	Acute effects systemic		
Consumers	Inhalation	65.3 mg/m ³	Chronic effects local		
Consumers	Dermal	125 mg/kg	Chronic effects systemic		
Workers	Inhalation	221 mg/m ³	Chronic effects local		
Consumers	Inhalation	260 mg/m ³	Acute effects local		
Consumers	Oral	5 mg/kg	Chronic effects systemic		

PNEC

reaction mass of ethylbenzene and m-xylene and p-xylene			
Route of exposure	Value		
Marine water	0.0044 mg/l		
Water (intermittent release)	0.01 mg/l		
Microorganisms in sewage treatment	1.6 mg/l		
Sea sediments	0.252 mg/kg		
Soil (agricultural)	0.852 mg/kg		
Freshwater sediment	2.52 mg/kg		
Drinking water	0.044 mg/l		

8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Mask with a filter against organic vapours in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid
Colour colourless
Odour specific
Melting point/freezing point -34 °C
Boiling point or initial boiling point and boiling range 135 - 143 °C



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

Xylene mixture of isomers

Creation date 24th August 2016

Revision date 28th May 2025 Version 9.0

Flammability data not available

Lower and upper explosion limit

bottom 1.0 % upper 7.0 %

Flash point 25 °C (uzavřený kelímek)

Auto-ignition temperature data not available
Decomposition temperature data not available
pH data not available
Kinematic viscosity data not available
Solubility in water data not available
Partition coefficient n-octanol/water (log value) data not available
Vapour pressure 10 hPa at 20 °C

Density and/or relative density

Density 0.867 g/cm³ at 20 °C Relative vapour density data not available Particle characteristics data not available

9.2. Other information

Oxidising properties It is not oxidising. Solid content (dry matter) <0.002 % volume

SECTION 10: Stability and reactivity

10.1. Reactivity

The substance is flammable.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the substance.

Acute toxicity

Harmful in contact with skin or if inhaled.

reaction mass of ethylbenzene and m-xylene and p-xylene						
Route of exposure	Parameter	Value	Exposure time	Species	Sex	Source
Oral	LD ₅₀	3523 mg/kg		Rat (Rattus norvegicus)	М	ECHA
Oral	LD ₅₀	>4000 mg/kg		Rat (Rattus norvegicus)	F	ECHA



SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended Xylene mixture of isomers Creation date 24th August 2016 Revision date 28th May 2025 Version 9.0

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

No data available for the substance. Based on available data the classification criteria are not met.

Germ cell mutagenicity

No data available for the substance. Based on available data the classification criteria are not met.

Carcinogenicity

No data available for the substance. Based on available data the classification criteria are not met.

Reproductive toxicity

No data available for the substance. Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause respiratory irritation.

Toxicity for specific target organ - repeated exposure

May cause damage to hearing organs through prolonged or repeated exposure.

reaction mass of	reaction mass of ethylbenzene and m-xylene and p-xylene						
Route of exposure	Parameter	Value	Exposure time	Result	Species	Sex	
Oral	NOAEL	500 mg/kg	2 years		Rat (Rattus norvegicus)		

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

Based on available data the classification criteria are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SECTION 12: Ecological information

12.1. Toxicity

Based on available data the classification criteria are not met.

Acute toxicity

reaction mass of	reaction mass of ethylbenzene and m-xylene and p-xylene						
Parameter	Value	Exposure time	Species	Environment	Source		
LC50	2.6 mg/l	96 hours	Fish (Oncorhynchus mykiss)		ECHA, p- xylen		
	1 mg/l	24 hours	Daphnia (Daphnia magna)		ECHA, o- xylen		



SAFETY DATA SHEET						
	according to Regulation (EC) No 1907/2006 (REACH) as amended					
	Xylene mixture of isomers					
Creation date	24th August 2016					
Revision date	28th May 2025	Version	9.0			

reaction mass of ethylbenzene and m-xylene and p-xylene						
Parameter	Value	Exposure time	Species	Environment	Source	
	1.3 mg/l	48 hours	Algae		ECHA, ethylbenzen	

Chronic toxicity

reaction mass of ethylbenzene and m-xylene and p-xylene						
Parameter Value Exposure time Species Environment Source						
	0.44 mg/l	72 hours	Algae		ECHA, p- xylen	

12.2. Persistence and degradability

No data available for the substance.

12.3. Bioaccumulative potential

No data available for the substance.

12.4. Mobility in soil

Based on available data the classification criteria are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on available data the classification criteria are not met. Does not contain any PBT or vPvB components. Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

Based on available data the classification criteria are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

07 01 08* other still bottoms and reaction residues

Packaging waste type code

15 01 10* packaging containing residues of or contaminated by hazardous substances

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

UN 1307

14.2. UN proper shipping name

XYLENES



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

Xylene mixture of isomers

Creation date 24th August 2016

Revision date 28th May 2025 Version 9.0

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

TTT

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No. 30
UN number 1307

Classification code

Safety signs 3+hazardous for the environment

F1

(D/E)



Tunnel restriction code

Air transport - ICAO/IATA

Packaging instructions passenger 355 Cargo packaging instructions 366

Marine transport - IMDG

EmS (emergency plan) F-E, S-D

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation. H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to the ears through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

Xylene mixture of isomers

Creation date 24th August 2016 Revision date 28th May 2025

Version 9.0

Guidelines for safe handling used in the safety data sheet

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. P210

No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water and soap. Immediately call a POISON CENTER/doctor. P310

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox Acute toxicity

ADR Agreement concerning the international carriage of dangerous goods by road

Aquatic Chronic Hazardous to the aquatic environment (chronic)

Aspiration hazard Asp. Tox. **Bioconcentration Factor** BCF CAS Chemical Abstracts Service

Regulation (EC) No 1272/2008 on classification, labelling and packaging of CLP

substance and mixtures

EC Identification code for each substance listed in EINECS

EINECS European Inventory of Existing Commercial Chemical Substances

EmS Emergency plan EU European Union

European Product Categorisation System **EuPCS**

Eye Irrit. Eye irritation Flam. Liq. Flammable liquid

TATA International Air Transport Association

International Code For The Construction And Equipment of Ships Carrying IBC

Dangerous Chemicals

ICAO International Civil Aviation Organization **IMDG** International Maritime Dangerous Goods IMO International Maritime Organization

INCI International Nomenclature of Cosmetic Ingredients ISO International Organization for Standardization **IUPAC** International Union of Pure and Applied Chemistry

LC50 Lethal concentration of a substance in which it can be expected death of 50% of the

population

LD50 Lethal dose of a substance in which it can be expected death of 50% of the

population

log Kow Octanol-water partition coefficient NOAEL No observed adverse effect level OEL Occupational Exposure Limits PBT

Persistent, bioaccumulative and toxic

PMT Persistent, mobile and toxic

Parts per million ppm

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

Skin Irrit.

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

Four-figure identification number of the substance or article taken from the UN UN number

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials



SAFETY DATA SHEET according to Regulation (EC) No 1907/2006 (REACH) as amended

Xylene mixture of isomers

Creation date 24th August 2016

Revision date 28th May 2025 Version 9.0

VOC Volatile organic compounds

vPvB Very persistent and very bioaccumulative

vPvM Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 9.0 replaces the SDS version from Monday, 17 February 2025. Changes were made in sections 2,9 and 16.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.