

according to Regulation (EC) No 1907/2006 (REACH) as amended

## Xylene mixture of isomers

Creation date	24th August 2016	Version	3.0
Revision date	31st March 2022		

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**  
 Substance / mixture Xylene mixture of isomers mixture  
 Other mixture names  
 Dimethylbenzene, Xylene
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**  
**Mixture's intended use**  
 Chemical production, analytical chemistry, laboratory synthesis, industrial applications.  
**Mixture uses advised against**  
 The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**  
**Supplier**  
 Name or trade name Ing. Petr Švec - PENTA s.r.o.  
 Address Radiová 1122/1, Praha 10, 102 00  
 Czech Republic  
 Identification number (CRN) 02096013  
 VAT Reg No CZ02096013  
 Phone +420 226 060 681  
 E-mail info@pentachemicals.eu  
 Web address www.pentachemicals.eu
- Competent person responsible for the safety data sheet**  
 Name Ing. Petr Švec - PENTA s.r.o.  
 E-mail info@pentachemicals.eu
- 1.4. Emergency telephone number**  
 European emergency number: 112

### SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**  
**Classification of the mixture in accordance with Regulation (EC) No 1272/2008**  
 The mixture is classified as dangerous.

Flam. Liq. 3, H226  
 Asp. Tox. 1, H304  
 Acute Tox. 4, H312+H332  
 Skin Irrit. 2, H315  
 Eye Irrit. 2, H319  
 STOT SE 3, H335  
 STOT RE 2, H373 (hearing organs)

Full text of all classifications and hazard statements is given in the section 16.

#### Most serious adverse physico-chemical effects

Flammable liquid and vapour.

#### Most serious adverse effects on human health and the environment

Causes skin irritation. May be fatal if swallowed and enters airways. May cause damage to hearing organs through prolonged or repeated exposure. May cause respiratory irritation. Causes serious eye irritation. Harmful in contact with skin or if inhaled.

according to Regulation (EC) No 1907/2006 (REACH) as amended

## Xylene mixture of isomers

Creation date 24th August 2016  
Revision date 31st March 2022 Version 3.0

### 2.2. Label elements

#### Hazard pictogram



#### Signal word

Danger

#### Hazardous substances

xylene  
ethylbenzene

#### Hazard statements

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H373 May cause damage to hearing organs through prolonged or repeated exposure.  
H312+H332 Harmful in contact with skin or if inhaled.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of water and soap.  
P310 Immediately call a POISON CENTER/doctor.

#### Supplemental information

Restricted to professional users.

### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 Registration number: 01-2119555267-33-0000	xylene	>99	Flam. Liq. 3, H226 Acute Tox. 4, H312, H332 Skin Irrit. 2, H315	1, 2
Index: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4	ethylbenzene	<26	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs)	2

according to Regulation (EC) No 1907/2006 (REACH) as amended

## Xylene mixture of isomers

Creation date	24th August 2016	Version	3.0
Revision date	31st March 2022		

### Notes

- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Substance with a Union workplace exposure limit.

Full text of all classifications and hazard statements is given in the section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

#### If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

#### If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

#### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

#### If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

### 4.2. Most important symptoms and effects, both acute and delayed

#### If inhaled

Cough, headache. May cause respiratory irritation.

#### If on skin

Causes skin irritation.

#### If in eyes

Causes serious eye irritation.

#### If swallowed

Irritation, nausea.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

according to Regulation (EC) No 1907/2006 (REACH) as amended

## Xylene mixture of isomers

Creation date	24th August 2016	Version	3.0
Revision date	31st March 2022		

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

##### Unsuitable extinguishing media

Water - full jet.

#### 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

#### 5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

#### 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

#### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

#### 6.4. Reference to other sections

See the Section 7, 8 and 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

Storage class

3A - Flammable liquids (flash point below 55 °C)

##### The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

#### 7.3. Specific end use(s)

not available

according to Regulation (EC) No 1907/2006 (REACH) as amended

## Xylene mixture of isomers

Creation date 24th August 2016  
Revision date 31st March 2022 Version 3.0

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

#### European Union

#### Commission Directive 2000/39/EC

Substance name (component)	Type	Value	Note
xylene (CAS: 1330-20-7)	OEL 8 hours	221 mg/m <sup>3</sup>	Skin
	OEL 8 hours	50 ppm	
	OEL 15 minutes	442 mg/m <sup>3</sup>	
	OEL 15 minutes	100 ppm	
ethylbenzene (CAS: 100-41-4)	OEL 8 hours	442 mg/m <sup>3</sup>	Skin
	OEL 8 hours	100 ppm	
	OEL 15 minutes	884 mg/m <sup>3</sup>	
	OEL 15 minutes	200 ppm	

#### 8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

##### Eye/face protection

Protective goggles.

##### Skin protection

Suitable material: fluororubber. Hand protection: Protective gloves resistant to the product (nitrile rubber). Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

##### Respiratory protection

Mask with a filter against organic vapours in a poorly ventilated environment.

##### Thermal hazard

Not available.

##### Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	-34 °C
Boiling point or initial boiling point and boiling range	135 - 143 °C
Flammability	data not available
Lower and upper explosion limit	
bottom	1,0 %
upper	7,0 %
Flash point	25 °C (uzavřený kelímeček)
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	data not available

according to Regulation (EC) No 1907/2006 (REACH) as amended

## Xylene mixture of isomers

Creation date	24th August 2016	Version	3.0
Revision date	31st March 2022		
Kinematic viscosity	data not available		
Solubility in water	data not available		
Partition coefficient n-octanol/water (log value)	data not available		
Vapour pressure	10 kPa at 20 °C		
Density and/or relative density			
Density	0,867 g/cm <sup>3</sup> at 20 °C		
Form			
<b>9.2. Other information</b>			
Solid content (dry matter)	<0,002 % volume		

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

not available

#### 10.2. Chemical stability

The product is stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Unknown.

#### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

#### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

#### 10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

#### Acute toxicity

Harmful in contact with skin or if inhaled.

xylene

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD50	4300 mg/kg		Rat	
Dermal	LD50	3200 mg/kg		Rabbit	

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data the classification criteria are not met.

according to Regulation (EC) No 1907/2006 (REACH) as amended

## Xylene mixture of isomers

Creation date	24th August 2016	Version	3.0
Revision date	31st March 2022		

### Carcinogenicity

Based on available data the classification criteria are not met.

### Reproductive toxicity

Based on available data the classification criteria are not met.

### Toxicity for specific target organ - single exposure

May cause respiratory irritation.

### Toxicity for specific target organ - repeated exposure

May cause damage to hearing organs through prolonged or repeated exposure.

### Aspiration hazard

May be fatal if swallowed and enters airways.

### 11.2. Information on other hazards

not available

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Acute toxicity

Data for the mixture are not available.

xylene

Parameter	Value	Time of exposure	Species	Environment
LC50	26.7 mg/l		Fishes (Pimephales promelas)	

### 12.2. Persistence and degradability

not available

### 12.3. Bioaccumulative potential

Not available.

### 12.4. Mobility in soil

Not available.

### 12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

### 12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### 12.7. Other adverse effects

Not available.

## SECTION 13: Disposal considerations

according to Regulation (EC) No 1907/2006 (REACH) as amended

## Xylene mixture of isomers

Creation date	24th August 2016	Version	3.0
Revision date	31st March 2022		

### 13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

#### Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

## SECTION 14: Transport information

### 14.1. UN number or ID number

UN 1307

### 14.2. UN proper shipping name

XYLENES

### 14.3. Transport hazard class(es)

3 Flammable liquids

### 14.4. Packing group

III - substances presenting low danger

### 14.5. Environmental hazards

not relevant

### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

### 14.7. Maritime transport in bulk according to IMO instruments

not relevant

#### Additional information

Hazard identification No.	30
UN number	1307
Classification code	F1
Safety signs	3



#### Air transport - ICAO/IATA

Packaging instructions passenger	355
Cargo packaging instructions	366

#### Marine transport - IMDG

EmS (emergency plan)	F-E, S-D
----------------------	----------



according to Regulation (EC) No 1907/2006 (REACH) as amended

## Xylene mixture of isomers

Creation date	24th August 2016	Version	3.0
Revision date	31st March 2022		

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

#### 15.2. Chemical safety assessment

not available

### SECTION 16: Other information

#### A list of standard risk phrases used in the safety data sheet

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to hearing organs through prolonged or repeated exposure.
H312+H332	Harmful in contact with skin or if inhaled.

#### Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P310	Immediately call a POISON CENTER/doctor.

#### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

#### Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization

according to Regulation (EC) No 1907/2006 (REACH) as amended

## Xylene mixture of isomers

Creation date	24th August 2016	Version	3.0
Revision date	31st March 2022		

IUPAC	International Union of Pure and Applied Chemistry
LC50	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD50	Lethal dose of a substance in which it can be expected death of 50% of the population
log Kow	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution from Ships
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
Skin Irrit.	Skin irritation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

### Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

### Recommended restrictions of use

not available

### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.  
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

### More information

Classification procedure - calculation method.

### Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.